

TECHNICAL DATA | CAT 7 uPVC COUPLING


Standards: Compatible with AS/NZS 1477 Pressure Pipe and AS/NZS 4765 Pressure Pipe Applications

Size Range: 200 mm - 375 mm

Materials: uPVC

Pressure Rating: PN 6, PN 12, PN16





| Size mm | D0 mm | d1 mm | d2 mm | d | т | L | Pressure Rating | Code |
|------------|----------|----------|----------|-------|--------|-------|--------------------|----------|
| 200 | 254.6 | 226.2 | 224.9 | 216.9 | 119.1 | 243 | PN12 | TCOUP200 |
| 225 | 287.9 | 251.3 | 249.9 | 241.9 | 131.65 | 268.3 | PN16 | TCOUP225 |
| 250 | 314.5 | 281.5 | 279.9 | 278 | 147 | 300 | PN16 | TCOUP250 |
| 300 | 354 | 316.7 | 314.9 | 306.9 | 164.3 | 335.4 | PN16 | TCOUP300 |
| 375 | 430.15 | 402 | 400 | 369.8 | 205.5 | 422.8 | PN6 | TCOUP375 |

Note:

Installation should always be performed by a licensed operator. It is the responsibility of the installer to check that both the pipe(s) and fitting(s) that are installed are compatible, only compatible materials should be joined together. It is the responsibility of the licensed installer to check the PN and SDR ratings marked on the fitting(s) and ensure that the pipe is compatible. Correct installation procedures should always be followed.

The drawings, materials and specifications outlined are subject to change without notice due to the continuous improvements and development of our product range.